



MODELO GLT16

Video Input	16CH BNC
Video Output	HDMI(1920*1080/1440*900/1280*1024/1024*768 VGA 1920*1080/1440*900/1280*1024/1024*768 CVBS (PAL : 720*576/NTSC : 720*480)
Audio Input	2CH RCA
Audio Output	1CH RCA
Video Compression	H.264
Video Preview Resolution	16CH D1
Recording Resolution	D1/CIF
Video BitRate	200kbps~1200kbps
Audio Compression	G.711

Ethernet	10M/100M Adaptive
Protocolo	TCP/IP, DHCP, PPPoE, UDP
Client-end	Cloudsee/WebCC/Android/IOS
Network	1 RJ45 10M/100M adaptive Ethernet Interface
USB Interface	2 USB 2.0 Interfaces
Serial Interface	1 RS-485 interface
Mobile OS	Android/IOS
Support Protocol	TCP/UDP
Screen Layout	1/2/4/8/9/16 Screens

HDD Type	SATA Interface
HDD Number	1pcs (up to 4T/pcs)
File Format	log : *.txt/picture : *.bmp/record : *.mp4
Log Number	2000
USB (backup)	Support U disk/Mobile HDD FAT32 format
Record Type	Manual,Scheduled,Alarm,Motion Detection
Record Mode	Cyclic Covering/Stop Recording
Playback Control	Play, Pause, Stop, Rewind, Fast play, Slow play, Digital zoom
Search Mode	All/Channel/Record Type/Date(Alone or Combined query)

Screen Layout	1/2/4/8/9/16 Screens
Alarm notification	Buzzer/Alarm device/PTZ call, Send alarm to client-end/E-mail alarm
Digital Zoom	Support
USB Recovery	Support
Voice Intercom	Support
Night Vision Mode	Support
Privacy Mask	Support
Video Loss Alarm	Support
Alarm Snapshot	Support
Playback Layout	4 Screens

Working Temperature	-10°C~+55°C
Working Humidity	10%~90%
Power Supply	DC12V
Power	≤15W (HDD not included)

Language	Multi-Language
Size(W×H×D)(mm)	295×45×235
Weight(g)	≤2000